

PMPWS WKREĆ-MET GUNFOAM ALLSEASON PMPWS WKREĆ-MET PIANA MONTAZOWA PISTOLETOWA MULTI

Date: 16.06.2010

Version nr.: 4

Revised: 15.08.2011

1. Identification of the mixture and of the company/undertaking

1.1. Product identifier: PMPWS WKREĆ-MET PIANA MONTAZOWA PISTOLETOWA MULTI

1.2. Relevant identified uses of the mixture and uses advised against:

Foam is used for installation of doors and windows, insulation and fixation of tubes, filling of holes and gaps, fixation of wall panels and roof stones, and for thermal insulation.

Adheres well to most building materials, with the exception of teflon, polyethylene and silicon surfaces. Cured foam is sensitive to UV-light and direct sunlight.

1.3. Details of supplier of the safety data sheet:

"WKREĆ-MET" Sp.z o.o. Sp.k.
ul.Wincentego Witosa 170/176
Kuźnica Kiedrzyńska
42-233 Mykanów

1.4. Emergency telephone number:

112

2. Hazards identification

2.1. Classification of the mixture

According to 67/548/EC



Harmful Xn,

R12 Extremely flammable

R20 Harmful by inhalation

R36/37/38 Irritating to eyes, respiratory system and skin

R40 Limited evidence of a carcinogenic effect

R42/43 May cause sensitization by inhalation and skin contact.

R48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation

R53 May cause long-term adverse effects in the aquatic environment

R64 May cause harm to breast-fed babies

Health



Extremely flammable (F+)

The vapor will irritate throat and lungs. Vapor is dangerous in huge amounts. Irritating to eyes. Occasionally, contact produces skin allergy.

Environment

May cause long-term adverse effects in the aquatic environment.

Fire

The propellant is inflammable and explosive.

2.2. Label elements

1. Persons already sensitised to diisocyanates may develop allergic reactions when using this product.
2. Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product.
3. This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used

2.2.1 Hazard symbol:



Harmful (Xn)



Extremely flammable (F+)

2.2.2 Hazardous ingredients: Consists isocyanate. See information applied by the manufacturer.

PMPWS WKREĆ-MET GUNFOAM ALLSEASON

PMPWS WKREĆ-MET PIANA MONTAZOWA PISTOLETOWA MULTI

2.2.3 R-phrases	R12	Extremely flammable	
	R20	Harmful by inhalation	
	R36/37/38	Irritating to eyes, respiratory system and skin	
	R40	Limited evidence of a carcinogenic effect	
	R42/43	May cause sensitization by inhalation and skin contact.	
	R48/20	Harmful: danger of serious damage to health by prolonged exposure through inhalation	
	R53	May cause long-term adverse effects in the aquatic environment	
	R64	May cause harm to breast-fed babies	
	2.2.4 S-phrases	S2	Keep out of the reach of children
		S9	Keep container in a well-ventilated place
S16		Keep away from sources of ignition -- No smoking	
S 23		Do not breathe gas/vapor	
S33		Take precautionary measures against static discharges.	
S36/37		Wear suitable protective clothing and gloves	
S45		In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).	
S51		Use only in well-ventilated areas	
2.3. Other hazards		No data available	

3. Composition/information on ingredients

3.1. Substances. Classification of substances

CAS-nr.	Chemical name	Content		Classification	
		Max.		According Directive 67/548/EEC	According Regulation 1272/2008 (CLP)
9016-87-9	Diphenylmethane-4',4'-diisocyanate	40	%	Xn; R20 R36/37/38 R42/43 R40 R48/20	Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2, H319 Resp. Sens. 1; H334 Skin Sens.1; H317 Carc. 2; H351 STOT SE 3; H335 STOT RE 2; H373
85535-85-9	C14-17, chlorinated paraffin	15	%	N; R50/53 R64 R66	Lact; H362 Aquatic Acute 1; H400 Aquatic Chronic 1; H410
75-28-5	Isobutane	8	%	F+; R12	Flam. Gas 1; H220 Press. Gas; H280
74-98-6	Propane	4	%	F+; R12	Flam. Gas 1; H220 Press. Gas; H280
115-10-6	Dimethylether	4	%	F+; R12	Flam. Gas 1; H220 Press. Gas H280

4. First aid measures

4.1 Description of first aid measures

Inhalation:	Move the exposed person to fresh air. Seek medical attention.
Skin contact:	Wash off with plenty of soap and water. Remove contaminated clothing. Seek medical attention if irritation or symptoms persist.
Contact with eyes:	Rinse eyes immediately with plenty of water, keeping the eye open. Seek medical attention.
Ingestion:	Do not induce vomiting or give water to drink. Seek medical attention and show product label.

PMPWS WKREŃ-MET GUNFOAM ALLSEASON

PMPWS WKREŃ-MET PIANA MONTAZOWA PISTOLETOWA MULTI

4.2. Most important symptoms and effects, both acute and delayed

Inhalation	Irritating to respiratory system.
Skin contact	Irritating to skin.
Contact with eyes	Irritating to eyes
Ingestion	May cause suffocation and vomiting.

4.3. Indication of any immediate medical attention and special treatment needed

As a general rule, and in all cases of doubt or when symptoms persist, always seek medical attention.

5. Fire fighting measures

5.1 Extinguishing media

5.1.1. Suitable extinguishing media:	Use extinguishing media appropriate the surrounding fire conditions. Use as appropriate: water spray, dry extinguishing media, foam and carbon dioxide.
5.1.2 Unsuitable extinguishing media:	No specific recommendations.

5.2. Special hazards arising from the mixture

Due to heat pressure in the aerosol-can is rising and there is a risk for explosion. In contact with fire product forms toxic fumes. Explosive propellant-air mix can be formed.

5.3. Advice for fire-fighters	No specific recommendations.
-------------------------------	------------------------------

6. Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation of the working area. Wear protective clothing, goggles and protective chemical resistant gloves classified under Standard EN374: protective gloves against chemicals and microorganisms. Avoid contact with skin and eyes. Do not inhale fumes. Use a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387), when you use product in the room which has a poor ventilation

6.2 Environmental precautions:

Spillages shall be absorbed by sand or cloths and stored in suitable container, or allow the foam to solidify. The waste must be handled in accordance with legal requirements.

6.3 Methods and material for containment and cleaning up

Fresh foam can be removed with acetone, cured foam only mechanically.

7. Handling and storage

7.1 Precaution for safe handling:

During operation, note that the product contains a flammable gas. Keep away from heat. Do not break or burn even after use. Should not be sprayed on a open flame or any incandescent material.

7.1.1. Protective measures	Ensure good ventilation. Keep away from heat. Keep away from sources of ignition- No smoking. Avoid contact with eyes and skin. Avoid static electricity. Make use of protective goggles and protective chemical resistant gloves classified under Standard EN374: protective gloves against chemicals and microorganisms.
----------------------------	--

7.1.2. Advice on general occupational hygiene

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.

7.2. Conditions for safe storage, including any incompatibilities

Storage: Keep in a cool, dry, well-ventilated area in an upright position away from direct sunlight and other heat sources. Do not store in the direct sunlight and not more than +50 °C. Storage: temperature +5°C to +30 °C.

7.3. Specific end use(s)

Foam is used for installation of doors and windows, insulation and fixation of tubes, filling of holes and gaps, fixation of wall panels and roof stones, and for thermal insulation. Adheres well to most building materials, with the exception of teflon, polyethylene and silicon surfaces. Cured foam is sensitive to UV-

PMPWS WKREŃ-MET GUNFOAM ALLSEASON PMPWS WKREŃ-MET PIANA MONTAZOWA PISTOLETOWA MULTI

light and direct sunlight.

8. Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit value

Components	CAS-No.	Type form of exposure	Control parameters
Dimethyl ether	115-10-6	TWA	1920 mg/m ³ 1000 ppm
Diphenylmethane-4,4'-diisocyanate	9016-87-9	No information	0,05 mg/m ³ 8 hours 0.005 ppm 8 hours
Propane	74-98-6	No information	Short time: 2000 mg/m ³ , 1100 ppm Long time: 1500 mg/m ³ , 800 ppm
Butane	106-97-8	No information	Short time: 1810 mg/m ³ , 750 ppm Long time: 1450 mg/m ³ , 600 ppm

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Ensure adequate ventilation, especially in confined areas.

8.2.2. Individual protection measures, such as personal protective equipment

Eye/face protection: During the work make use of protective goggles

Skin protection: During the work make use of protective chemical resistant gloves classified under Standard EN374: protective gloves against chemicals and microorganisms.

Respiratory protection: Use the product only in well-ventilated rooms. Do not inhale fumes. When using in poorly ventilated area, wear a suitable filter of the mask (ie type A1 in accordance with EN 14387).

8.2.3. Environmental exposure controls Do not let into environment. May cause long-term adverse effects in the aquatic environment.

9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Aerosol
Colour	Pale beige
Odour	Characteristic
pH	Not applicable
Melting point / freezing point	Not relevant
Boiling point	Over +100 °C
Flash point	Below -20 °C
Evaporation rate	Not relevant
Flammability	Above +100 °C
Explosion limits	Low: 2 % vol, high: 10% vol.
Vapor pressure	5 Bar/+20 °C 10 Bar/+50 °C
Vapor density	Not applicable
Relative density	1.1 g/ml/+20 °C
Solubility in water	insoluble
Solubility in other solvents	In acetone soluble
Partition coefficient: n-octanol/water	Not applicable
Auto-ignition temperature	Not applicable
Decomposition temperature	+ 200 °C
Viscosity	ca 500 cP/+20 °C
Explosive properties	Contains flammable gases.
Oxidizing properties	Not applicable

9.2. Other information

Lack of data

PMPWS WKREŃ-MET GUNFOAM ALLSEASON
PMPWS WKREŃ-MET PIANA MONTAZOWA PISTOLETOWA MULTI
10. Stability and reactivity

- 10.1. Reactivity** The mixture is not reactive under recommended storage and handling conditions (see section 7).
- 10.2. Chemical stability** The mixture is stable under recommended storage and handling conditions (see section 7).
- 10.3. Possibility of hazardous reactions** In case of fire, the product can create corrosive and hazard gases.

10.4 Conditions to avoid:

An aerosol container is under pressure, do not expose to heat. Do not store in the sun, and not more than +50 °C. Do not break or burn even after use. Should not be sprayed on a open flame, or any incandescent material.

10.5. Incompatible materials: No data available

10.6. Hazardous decomposition products: In case of fire, the product can create corrosive and hazard gases.

11. Toxicological information
11.1. Information on toxicological effects
11.1.1. Substances

11.1.1.1. The relevant hazard classes for which information shall be provided are:

(a) Acute toxicity

	Dimethyl ether	Diphenylmethane-4',4'-diisocyanate	Isobutane / propane
Acute Oral toxicity	Not applicable	LD50 (rat): > 2.000 mg/kg	Not applicable
Acute Dermal toxicity	Not applicable	Not applicable	Not applicable
Acute Inhalation toxicity	LC50 (rat): 164 000 ppm Respiratory effects Anaesthetic effects Central nervous system depression narcosis Cardiac irregularities Coma.	LC50 (rat): 490 mg/m ³ 4h Tested substance: Aerosol Saturated vapour concentration at 25 °C: 0,09 mg/m ³	Not applicable

(b) Skin corrosion / irritation

	Dimethyl ether	Diphenylmethane-4',4'-diisocyanate	Isobutane / propane
Skin irritation	Not tested on animals Classification: Not classified as irritant Result: No skin irritation Not expected to cause skin irritation based on expert review of the properties of the substance.	Rabbit Result: No skin irritation Method: OECD test guide 404	No skin irritation

(c) Serious eye damage / irritation

	Dimethyl ether	Diphenylmethane-4',4'-diisocyanate	Isobutane / propane
Eye irritation	Not tested on animals Classification: Not classified as irritant Result: No eye irritation Not expected to cause eye irritation based on expert review of the properties of the substance.	Rabbit Result: No eye irritation Method: OECD test guide 405	No eye irritation

(d) Respiratory or skin sensitization

	Dimethyl ether	Diphenylmethane-4',4'-diisocyanate	Isobutane / propane
Sensitization	Not tested on animals	Result: May cause	No

PMPWS WKREŃ-MET GUNFOAM ALLSEASON
PMPWS WKREŃ-MET PIANA MONTAZOWA PISTOLETOWA MULTI

	Classification: Not a skin sensitizer Not expected to cause eye irritation based on expert review of the properties of the substance.	sensitization by inhalation and skin contact Isocyanate vapor may cause asthmatic allergy	sensitization effect
--	--	--	----------------------

(e) Germ cell mutagenicity

	Dimethyl ether	Diphenylmethane-4',4'-diisocyanate	Isobutane / propane
Germ cell mutagenicity	Animal testing did not show any mutagenic effects. Tests on bacterial or mammalian cell cultures did not show mutagenic effects.	Lack of data	Not applicable

(f) Carcinogenicity

	Dimethyl ether	Diphenylmethane-4',4'-diisocyanate	Isobutane / propane
Carcinogenicity	Animal testing did not show any carcinogenic effects.	Lack of data	Not applicable

(g) Reproductive toxicity

	Dimethyl ether	Diphenylmethane-4',4'-diisocyanate	Isobutane / propane
Reproductive toxicity	No toxicity on reproduction May cause cardiac arrhythmia. Rapid evaporation of the liquid may cause frostbite.	Lack of data	Not applicable

(h) STOT-single exposure

Lack of data

(i) STOT-repeated exposure

Lack of data

PMPWS WKREŃ-MET GUNFOAM ALLSEASON
PMPWS WKREŃ-MET PIANA MONTAZOWA PISTOLETOWA MULTI
12. Ecological information
12.1. Toxicity

	Dimethyl ether	Diphenylmethane-4',4'-diisocyanate	Isobutane / propane
Toxicity to fish	LC50 /96h/ Poecilia reticulata (guppy): > 4000 mg/l	LC50 /96h/ danio rerio: > 1.000 mg/l Method: OECD test guide 203	Not applicable
Toxicity to aquatic invertebrates	EC50 /48h/ Daphnia: > 4000 mg/l LC50 /48h/ Daphnia: 755,5 mg/l	EC50 /24h/ Daphnia magna: > 1.000 mg/l Method: OECD test guide 202	Not applicable
Chronic toxicity to fish	Due to its physical properties, there is no potential for adverse effects.	Lack of data	Lack of data
Toxicity to bacteria	Lack of data	EC50 /3h/ activated sludge: >100 mg/l Method: OECD test guide 209	Lack of data

12.2. Persistence and degradability

	Dimethyl ether	Diphenylmethane-4',4'-diisocyanate	Isobutane / propane
Persistence and degradability	Method: Closed Bottle test According to the results of tests of biodegradability this product is not readily biodegradable.	Biodegradability 28 days 0 %. Method: OECD test guide 302 C	Not applicable

12.3. Bio-accumulative potential:

	Dimethyl ether	Diphenylmethane-4',4'-diisocyanate	Isobutane / propane
Bioaccumulation	No data available	No data available	Not applicable

12.4. Mobility in soil:

	Dimethyl ether	Diphenylmethane-4',4'-diisocyanate	Isobutane / propane
Mobility in soil	Koc: 7,759	No data available	Not applicable

12.5. Results of PBT and vPvB assessment:

	Dimethyl ether	Diphenylmethane-4',4'-diisocyanate	Isobutane / propane
PBT and vPvB assessment	This substance is not considered to be persistent, bio accumulating nor toxic (PBT). The substance is not considered to be very persistent nor very bio accumulating (vPvB).	No data available	Not applicable

12.6. Other adverse effects

Dimethyl ether	Diphenylmethane-4',4'-diisocyanate	Isobutane / propane
Ozone depletion potential: 0 Global warming potential (GWP): 1	Not applicable	Not applicable

13. Disposal considerations
13.1. Waste treatment methods

PMPWS WKREŃ-MET GUNFOAM ALLSEASON

PMPWS WKREŃ-MET PIANA MONTAZOWA PISTOLETOWA MULTI

- 13.1.1. Product / Packaging disposal: The product and packages must be handled in accordance with national and local requirements.
- 13.1.2. Waste treatment options: Foam bottles are recyclable.
- 13.2. Additional information** No specific recommendations.

14. Transport information

- 14.1 UN number** 1950
- 14.2 Packing Group** Not known
- 14.3 Road ADR** Inflammable aerosol Class 2/5F
- 14.4 Railway RID** Inflammable aerosol Class 2/5F
- 14.5 Transport by sea GGVSee/IMDG-Code** Aerosol Class 2
- 14.6 Air transport ICAO-TI/IATA-DGR** -

15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Not applicable

15.2. Chemical safety assessment

Chemical safety assessment has been carried out for dimethyl ether and still at work for diphenylmethane-4',4'-diisocyanate.

16. Other information

16.1. Date of preparation of the latest version of the SDS

Written in the beginning of the safety data sheet.

16.2. Abbreviations and acronyms

TWA: Time Weighted Average

LC50: Lethal Concentration Medium

EC50: effective Concentration Medium

STOT: Specific target organ toxicity

PBT: Persistent, bioaccumulativ and toxic

vPvB: very persistent very bioaccumulative

Acute Tox.4: Acute Toxicity: inhaled- Category 4

Carc. 2: Carcinogenicity- Category 2

Eye Irrit. 2: Serious eye damage/ eye irritation- Category 2

Resp. Sens. 1: Respiratory sensitization- Category 1

Skin Irrit.2: Skin corrosion/irritation- Category 2

Skin Sens. 1: Skin sensitization- Category 1

STOT RE 2: Specific target organ toxicity (repeated exposure): inhalation- Category 2

STOT SE 3: Specific target organ toxicity (single exposure): inhalation- Category 3

Flam. Gas 1: Flammable Gas- category 1

Press. Gas: Gases under pressure

Aquatic Acute 1: Aquatic Acute- Category 1

Aquatic Chronic 1: Aquatic Chronic- Category 1

16.3. Key literature references and sources of data

The safety data sheet meets the requirements of the European Parliament and Council Regulation (EC) No.1907/2006 and the Chemicals Act of the Republic of Estonia and regulation No 130 of Minister of Social Affairs.

16.4. Classification and classification procedure used for mixtures

16.5. Relevant R-phrases and/or H-statements (specified in clause 3)

According Directive 67/548/EEC

R12 Extremely flammable

R20 Harmful by inhalation.

R36/37/38 Irritating to eyes, respiratory system and skin.

R40 Limited evidence of a carcinogenic effect

SAFETY DATA SHEET

PMPWS WKREŃ-MET PIANA MONTAZOWA PISTOLETOWA MULTI

PMPWS WKREŃ-MET GUNFOAM ALLSEASON

PMPWS WKREŃ-MET PIANA MONTAZOWA PISTOLETOWA MULTI

R42/43 May cause sensitization by inhalation and skin contact.

R48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation.

R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment

R53 May cause long-term adverse effects in the aquatic environment

R64 May cause harm to breast-fed babies

R66 Repeated exposure may cause skin dryness or cracking

According Regulation 1272/2008 (CLP)

H220 Extremely flammable gas

H280 Contains gas under pressure; may explode if heated

H315 Cause skin irritation

H317 May cause an allergic skin reaction

H319 Causes serious eye irritation

H332 Harmful if inhaled

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled

H335 May cause respiratory irritation

H351 Suspected of causing cancer

H362 May cause harm to breast-fed children.

H373 May cause damage to organs through prolonged or repeated exposure if inhaled.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

16.6. Training advice

No specific recommendations.

16.7. Further information

No specific recommendations.